Glass Door: DLS95PG

Overview

Our intuitive range refrigerators feature built-in wireless monitoring software, enabling you to access the refrigerator's performance remotely.

Plus, our bespoke touchscreen controller, designed specifically for the end user with simple access to key information.



Key Features



Advanced Controller Easy to use touch screen controller, with no awkward buttons to press



Connected Wireless temperature monitoring built-in



Dual Temperature Probes

View your daily minimum and maximum temperatures in one touch



Battery Back-Up A/V alarms should your temperature stray or the door be left open



Antimicrobial Protection

Biocote® handle helping protect from microbes such as E. coli, Campylobacter, Salmonella and MRSA



Self-Closing Doors Fitted with self-closing hinges to help avoid any temperature loss

DLS95PG - Product Specification

NeedDSSP GCross Capacity Culture)65Unit External Depth form)630 (culture)Unit External Depth form)630 (culture)Unit External Depth form)630Packed Widh (rom)930Packed Widh (rom)640Packed Widh (rom)740Packed Widh (rom)	Counter Top	
Sesses9sNet Capacity (Litres)9sNet Capacity (Litres)8sUnit External Pepth form)65/ Soci lar doUnit External Pepth form)65/ Soci lar doPacked Bepth form)600Packed Bepth form)630Packed Bepth form)630Derors formFormoreRepacked Bepth form)730Derors formFormoreDerors formFormoreDerors formNon-MerchantDerors formNon-MerchantDerors formYesDerors formYes<	Model	DLS95PG
Net Gaschy Glires)NitUnit External Medit form)SD0Unit External Medit form)SD0Rocked Weldt form)SD0Packed Dept form)SD0Packed Weldt form)SD0Temper External Formic form (WCDACH)SD0Temper External Formic form)SD0Temper External Formic form (WCDACH)SD0Der StellSD0Der StellSD1Adjutatier External Formic formSD1Robershine Display On PanelSD1Der StellSD1Adjutatier External Formic formSD1Robershine Display On PanelSD1Stell StellSD2Adjutatier External Formic formSD2Robershine Display On PanelSD1Stell StellSD2Adjutatier External Formic formSD2Robershine Display On PanelSD2Stell StellSD2Adjutatier Ext		
Unit Estema Neght from)500Unit Estema Neght from)630 (acc) tarulle)Unit Estema Neght from)630Packed Neght from)640Packed Neght from)640Packed Neght from)640Packed Neght from)630Packed Neght from)630Packed Neght from)630Packed Neght from)640Packed Neght from)630Packed Neght from)750Packed Neght from)750 </th <th></th> <th></th>		
Unit External Neight form)EXP (see) function)Unit External Neight form)550Packed Winft form)640Packed Neight form)70Packed Neight form)		
Init Exemal Height (am)60Packed Writh (mm)60Packed Writh (mm)60Packed Writh (am)32Packed Writh (am)320Packed Writh (am)320Internal Dimensions (am) Writh 20320Internal Dimensions (am) Writh 20320Internal FinishProconted stellInternal FinishProconted stellInternal FinishProconted stellInternal FinishProconted stellInternal FinishProconted stellDoor TypeRight hand HingelDoor TypeRight hand HingelDoor Stell197Replaceable Door SealYesOpen Door SeasoYesLockYes / MonancalAdjustable FeetOnePortholeYesPorthole SteeYesRemote Alarm ContactsYesAddite AlarmsYesNumber Of Shelves2Number Of Shelves10/2004/48Basket Stae10/2004/48Basket St		
Packed Vidth fum)300Packed Vidth fum)640Packed Vidght fun)640Packed Vidght fun)800Packed Vidght fun)420.300/50Internal Dirensions fum) Vixobal420.300/50Temperature Range<200.905Cetternal FinishPrecetatistatelInternal Precisions fum) VixobalPrecetatistatelInternal Precisions fum) VixobalPrecetatistatelInternal Precisions fum) VixobalPrecetatistatelInternal Precisions fum) VixobalPrecetatistatelInternal PrecisionsReplaceable Door SealOpen Door SealVisoOpen Door SealVisoOpen Door SealVisolParthole FeetOneParthole SeaVisolParthole SeaVisolParthole SeaVisolParthole SeaVisolNumber Of Shelf VisolSocial SeaNumber Of Shelf VisolSocial SeaNumber Of Shelf VisolSocial SeaNumber Of Shelf VisolSocial SeaNumber Of Shelf VisolSocial SeaInterial VisolVisol AlarmaShelf MarcialVisol Social SeaInterial VisolSocial SeaNumber Of Shelf VisolSocial SeaInterial VisolSocial SeaNumber Of ShelfsInterial SeaInterial VisolSocial SeaShelf MarcialVisol Social SeaInterial FinishSocial SeaShelf MarcialSocial SeaShelf MarcialSocial SeaInterial Sea <th></th> <th></th>		
Packed Height (mm)6/0Packed Height (mm)6/0Packed Weight (ba)32Internal Dimensions (mm) (Wsbxh)43b/330/610Temperature Range4/C in 6/G.External FinishProcotal SkelIternal FinishProcotal SkelIternal FinishProcotal SkelDoor TypeRight hard HingelDoor TypeRight hard HingelDoor Stel13/7Replaceable Door SealYesOpen Door SensorYesCarlow (Street Market Mark		
Packed Weight Gg0G90Packed Weight Gg0S2Iternal Dimensions (mm) (VxDxt)AdDxSDxSG0Temperature Range-XCto r8CExternal FinishPrecated stallIternal FinishPrecated stallIternal FinishPrecated stallDoor Type of PaskABX / S00 (Grad)Door Type of PaskRegist (Grad)Door Type Of PaskRegist (Grad)Door Type Of PaskRegist (Grad)Door Type Of PaskRegist (Grad)Door SyleGrad / Sen /		
Packed Weight 6g032Internal Dimensions (mm) (WxDaH)420x30x500External FinishProcested scielInternal FinishProte K AummunnType of PasiteHifs froad giaabDoor TypeRM Hand FingdDoor SensorYesChekYesPartheleYesPartheleNonAdjustable FeetNonPortholeYesPartheleYesParthele StageNonRemote Alam ContactsYesAudho AarmsYesNumber Of Stafe Folgon3Number Of Stafe FolgonSaNumber Of Stafe Folgon3Staf StafAfd xa00Staf StafAfd xa00Staf StafAfd xa00Staf StafNonNumber Of Stafe Folgon1Basket MaterialNo Cacuel wireInterior LiphtYesLight YapeICDLight YapeICDStaf StafNoStaf Staf <th></th> <th></th>		
Internal Dimensions (mm) (WxDxH0) 430x30x400 Temperture Range 42 to 48C External Finish Pre-coded skel Internal Finish Prestic A Alumnium Door Type Right hand Hings do godol Door Type Right hand Hings do godol Door Type Right hand Hings do Door Style Caka / Safl Coong Open Door Depth 157 Replacable Door Seal Ves Door Style One Dorthole Ves Dorthole Ves Dorthole Ves Dorthole Ves Porthole Size Tomm Temperature Disploy On Panel LED / Touchscreen Remote Alarm Contacts Ves Number Of Shele Positions 3 Shelf Size 440 x000 Shelf Material PVC coated wire Number Of Backels 1 Backel Size 440x20Xa48 Baskel Material PVC coated wire Number Of Backels 1 Baskel Size 440x20Xa48 </th <th></th> <th></th>		
Temperture Range2×2 to 40°External FinishPrecoated StatedInternal FinishPrastic AluminumType of PlasticHills Troad grade)Door TypeRapht Mark HingedDoor TypeRapht Mark HingedDoor StyleGiss / Self CosingOpen Door SensorVisCharles Door SensorVisLockVis / MechanicalAdjustable FeetOnePortholeYesPorthole StateIisminTemperature Display On PanelLib / TouchscreenTemperature Display On PanelLib / TouchscreenTemperature Display On PanelVisAuthole AlarmsVisNumber Of Shelf Poiltions3Shef State44x 400Shef State1Basket State10×250448Basket State10×250448Basket StateVisLight AlarnsVisShef StateNosShef StateNosShef StateNosShef StateNosShef StateNosShef MaterialVic control wireNumber Of Shef Poiltons3Shef StateNosShef StateN		
External FinishPrecodet shellInternal FinishPrescient SchummumType of PasticHile Sfood grade]Door TypeBayt hand HingedDoor StydGas / Sel CosingOpen Door Depth137Reptacable Door SealYesLockYes / MchancalAdjustable FeelOnePortholeYesPorthole SizeIformTemperature Display On PanelLD / YourKoreenRendication ConductYesAdubte AlarmsYesAdubte AlarmsYesAdubte AlarmsYesAdubte AlarmsYesNumber Of Shelvs2Number Of Shelvs2Shelf Size44x 400Shelf SizeAdva AlorShelf SizeAdva AlorShelf SizeAlorShelf SizeAlor SocialShelf SizeNone CottonlierFanYesSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeNoSpark FreeSpark NoSpark FreeNoSpark FreeNoSpark Free		
Internal Finish Pastic & Auminium Type of Plastic HPS (Focd grado) Door Type Right Inna Hinged Door Style Glass / Saft Closing Open Door Depth 137 Replaceable Door Seal Vis Open Door Depth 137 Replaceable Door Sensor Ves Lock Ves / McMandal Adjustable Feet One Porthole Size Term Temperature Display On Panel LED / Touchscreen Temperature Atam Ves Remote Alarm Contacts Yes Audhic Atarns Yes Number Of Shelves 2 Number Of Shelves 3 Shelf Material PVC coated vire Number Of Shelves 1 Shelf Material PVC coated vire Number Of Shelves 1 Shelf Material PVC coated vire Light Atvarda PVC coated v		
Type of PlasticHIPS (Flood grade)Door TypeRight hand HingedDoor StypeGles (SF Glosm, GOpen Door Depth137Replacatle Door SalYesOpen Door SensorYesLockYes / MechancialAdjustable FeetOnePortholeYesPortholeYesPorthole SizeIformmTamperature Display On PanelLED (TruchscreenTamperature Display On PanelLED (TruchscreenTamperature OtatisteYesAudible NarmsYesMombel Of Stelves2Number Of Stelves2Stelf Stel444 × 400Stelf Stel444 × 400Stelf Stel444 × 400Stelf MaterialPVC coated wireNumber Of Stelves2Stelf MaterialPVC coated wireNumber Of Stelves40x250x443Basket Size40x250x443Basket Size40x250x443Basket SizeNoController TypeLEDLight PrypeLEDLight ReplayNoController OnecultyWreless / SD DownloadNumber Of Probes2Probe TypeLift / AuriadDor Switch / CortrollerEnterRaft ReportNoController OnecultyWreless / SD DownloadNumber Of Probes2Probe TypeLift AuriadNumber Of Probes2Probe TypeLift AuriadNumber Of Probes2Probe TypeLi		
Door TypeRight hand HingedDoor StyleGlas / Self ClosingOpen Door Depth1137Replacable Door SealYesOpen Door SensorYesLockYes / MechanicalAdjustable FeetOnePortholeYesPorthole SizeIsmmTemperature Display On PanelLED / TouchscreenTemperature AtamYesRenote Alam ContactsYesAudible AlarmsYesNumber Of Shelves2Number Of Shelves1Sheff Size444x 400Sheff Size40x2Sox/H8Basket MaterialPVC cated wireNumber Of Shelves1Basket Size40x2Sox/H8Basket SizePVC cated wireLight ActivationDoor Switch / ControlerFanYesSpark FreeNoDeforts StringAutoControler ConnectivityWreless / SDD ControlerFanYesSpark FreeNoDeforts StringAutoControler ConnectivityWreless / SDD ControlerFan2Probe TypeAir / LoadAndreid Freeperature RangeNoNumber Of Shelpes2Probe StringAir CondaGaster Backet MaterialNoControler ConnectivityWreless / SDD ControlerFanSoler2Probe TypeAir LoadAutoSDEControler ConnectivityWreless / SDD ControlerRanges String <td< th=""><th></th><th></th></td<>		
Door StyleGless / Self ClosingOpen Door Depth1137Replaceable Door SensorYesOpen Door SensorYesLockYes / MchanicalAdjustable FeetOnePortholeYesPortholeYesPorthole SizeIorumTemperature Display On PanelLED / TouchscreenRemote Alarm ContactsYesAudible AlarmsYesNumber Of Shelves2Number Of Shelves2Shelf Stac4/4 x 400Shelf Stac1000 SourceNumber Of Shelves1Basket MatrialPVC Coated wireNumber Of Shelves1Basket Stace4/02OXIABBasket Stace1000 Soutch / ControllerFenYesController TypeAudioDoff Shelves2Number Of Shelves2DefinationDoor Switch / ControllerFanYesShelf MatrialPVC Coated wireInterior LightYesLight ActuationDoor Switch / ControllerFanYesController TypeDigit/ WirelesBatery Back UpYesController ConnectivityWireles / SD DownloadNumber Of Probes2Probe TypeAir (LoadAndient Temperature Range10-32CReringerant Yes2024OvVerlages Supply2024OvVolages Supply2024OvFrequency (Hz)Solt ZProperative Range10-32C		
Open Door Depth1137Replacable Door SealYesLockYes / MachanicalAdjustable FeetOnePortholeYesPorthole SizeIornmTemperature Display On PanelLED / TouchscreenTemperature AtamYesRemote Atam ContactsYesNumber Of Shelves2Shelf MaterialPVC coated wireNumber Of Shelves1Basket Size444 x 400Shelf MaterialPVC coated wireNumber Of Baskets1Basket Size440x250x148Basket Size40x250x148Basket Size40x250x148		
Replaceable Door SensorYesOpen Door SensorYes / McchanicalAdjustable FeetOnePortholeYesPorthole SizeIformTemperature Display On PanelLED / TouchscreenTemperature Display On PanelYesAudible AlarmsYesAudible AlarmsYesAudible AlarmsYesShall AlarmsYesMumber Of Shelves2Shelf Size444 x 400Shelf Size444 x 400Shelf Size444 x 400Shelf Size410x250x48Basket Size410x250x48Basket Size410x250x48Basket Size410x250x48Basket Size10Door Switch / ControllerFanYesUight ActivationDoor Switch / ControllerFanYesController TypeDigital / WreiesBattery Back UpYesController TypeDigital / WreiesController TypeAr/ LoadNumber Of Probes2Probe TypeAr/ LoadAntimer ConnectivityWreies / SD DownloadNumber Of Probes2Probe TypeR600aPlug TypeUKVolage Supply2020VFrequency Reb50K 2Frequency Reb50K 2No2Volage Supply2020VFrequency Reb50K 2Frequency Reb50K 2Frequency Reb50K 2Rest Supply50K 2Solval Humber Diff		
Open Door SensorYesLockYes/MechanicalAdjustable FoetOnePortholeYesPorthole SizeIformTemperature Display On PanelLED/ TouchscreenTemperature Display On PanelKeD/ TouchscreenMatter Display On PanelYesAudible Alarm ContactsYesVisual AlarmsYesVisual AlarmsYesNumber Of Shelves2Number Of Shelves3Shelf Size44/4 x 400Shelf MaterialPVC coated wireNumber Of Bakets1Basket Size410\u250xl48Basket MaterialPVC coated wireLiterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDiglai / WrelessBattery Back UpYesVinder Of Shelpes2Probe TypeAutoController TypeDiglai / WrelessBattery Back UpYesProbe TypeAutoController ConnectivityWireless / SD DownloadMumber Of Probes2Probe TypeBioConaPlay TypeUKVolage Supply20:2040VFrequency RivDSDriezInsulation Thickness37		
LockYes / MechanicalAdjustble FeetOnePortholeYesPorthole SizeHommTemperature Display On PanelLED / TouchscreenTemperature Display On PanelLED / TouchscreenRemote Alarm ContactsYesAudible AlarmsYesVisual AlarmsYesNumber Of Shelves2Number Of Shelves2Number Of Shelves2Number Of Shelves2Number Of Shelves1Basket MaterialPVC coated wireNumber Of Baskets1Basket MaterialPVC coated wireInterior LightYesLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBasket Statting1Basket StattingAutoController TypeRoOanFarYesController TypeDigital / WirelessBatter StattingAitoController TypeRoOanRefrigerant TypeRoOanProbe TypeNoDornoladNumber Of Probes2Probe TypeRefrigerant TypeRoOanPitag TypeUKVottag Supply20:20/VFrequency (Hz)Sold ZInsulation Thickness37		
Adjustable FeetOnePortholeYesPorthole SizeIformTemperature Display On PanelLED / TouchscreenTemperature AlarmYesAudible AlarmSYesAudible AlarmSYesNumber Of Shelves2Number Of Shelves3Shelf Size444 x00Shelf Size440x200x148Basket Size440x20x148Basket Size40x20x148Basket Size1Basket Size1Basket Size100x1000000000000000000000000000000000		
PortholeYesPorthole SizeFirmPorthole SizeFirmPorthole SizeFirmRemote AlarmYesRemote Alarm ContactsYesAudible AlarmsYesAudible AlarmsYesNumber Of Shelves2Number Of Shelf Positions3Shelf Size444 x 400Shelf Size444 x 400Shelf Size444 x 400Shelf MaterialPVC coated wireNumber Of Baskets1Basket MaterialPVC coated wireInterior LightYesLight TypeLiDLight TypeLiDDefore StelingAudoSpark FreeNoDefored StelingAudoController ConnectivityWireless / SD DownloadBather Size2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefreeRécooaProbe TypeLikVeriage Supply220-20/VPrequency (Hz)SizeNother StelingAir / LoadAmbient Temperature Range37		
Porthole SizeI6mmTemperature Display On PanelLED / TouchscreenTemperature AlarmYesRemote Alarm ContactsYesAudible AlarmsYesAudible AlarmsYesNumber Of Shelves2Number Of Shelves3Shelf Size444 x 400Shelf Size444 x 400Shelf MaterialPVC coated wireNumber Of Baskets1Basket Size410x250x148Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFenNoDefrost SettingAutoController ConnectivityWreless / SD DownloadNumber Of Probes2Probe TypeDigital / WrelessBatter J Back UpYesController ConnectivityWreless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR600aPlug TypeUKVoltage Supply220-240VFrequency (Ke)SoHzInsulation Thickness37		
Temperature Display On PanelLED / TouchscreenTemperature AlarmYesRemote Alarm ContactsYesAudible AlarmsYesVisual AlarmsYesNumber Of Shelves2Number Of Shelves3Shelf Size444 x 400Shelf Size444 x 400Shelf Size444 x 400Shelf Size40x250x148Basket Size40x250x148Basket Size40x250x148Basket MaterialPVC coated wireLight YpeLEDLight XprKesSpark FreeNoDefroit SetingAutoController TypeDigital / WirelessBatter Yack UpYesController OnculvityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range0 - 32CRefigerant TypeUKVolage Supply202040VFrequency (Hz)Spark FreeInsulation Thickness37		
Temperature AlarmYesRemote Alarm ContactsYesAudible AlarmsYesAudible AlarmsYesNumber Of Shelves2Number Of Shelves3Shelf Size444 x 400Shelf AlarialPVC coated wireNumber Of Bakets1Basket Size40x250x148Basket Size40x250x148Basket Size40x250x148Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigit / WrelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10-32CRefrigerant TypeUKVoltage Supply20240VFrequency (Hz)SoHzInsulation Thickness37		
Audible AlarmsYesVisual AlarmsYesNumber Of Shelves2Number Of Shelves3Shelf Soit3Shelf Size444 x 400Shelf MaterialPVC coated wireNumber Of Baskets1Basket Size410x250x148Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight TypeDor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBatery Back UpYesController ToppeAir/ LoadAmbient Temperature Range10.32CRefrigerant TypeUKVoltage Supply202040VFrequency (Hz)Soft z<Insulation Thickness37		
Visual AlarmsYesNumber Of Shelves2Number Of Shelf Positions3Shelf Size444 x 400Shelf Size444 x 400Shelf MaterialPVC coated wireNumber Of Baskets1Basket Size410x250x148Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController TypeAutoController TypeDownloadNumber Of Probes2Probe TypeAr/ LoadAmbient Temperature Range10 - 32CRefrigerant TypeR6O0aPlug TypeUKVoltage Supply520-240VFrequency (Hz)50HzInsulation Thickness37	Remote Alarm Contacts	Yes
Number Of Shelves2Number Of Shelf Positions3Shelf Size444 x 400Shelf MaterialPVC coated wireNumber Of Baskets1Basket Size410x250x148Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController TypeDigital / WirelessBattery Back UpXer SolutionAutoControllerFree Porbe TypeAir / LoadAmbient Temperature Range10 · 32CRefrigerant TypeRécOoaPlug TypeUkVoltage Supply220-240VFrequency (Hz)Solutal /Insulation Thickness37	Audible Alarms	Yes
Number Of Shelf Positions3Shelf Size444 x 400Shelf MaterialPVC coated wireNumber Of Baskets1Basket Size410x250x148Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBatter y Back UpYesController Of Probes2Probe TypeAir / LoadAmblent Temperature Range10 - 32CRefrigerant TypeUKVoltage Supply220-240VFrequency (Hz)SoHzInsulation Thickness37	Visual Alarms	Yes
Shelf Size444 x 400Shelf MaterialPVC coated wireNumber Of Baskets1Basket Size410x250x148Basket MaterialPVC coated wireInterior LightVesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController ConnectivityWirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeUKVoltage Supply220-240VFrequency (Hz)SOHzInsulation Thickness37	Number Of Shelves	2
Shelf MaterialPVC coated wireNumber Of Baskets1Basket Size410x250x148Basket MaterialPVC coated wireInterior LightYesLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefigerant TypeK600aPlug TypeUKVoltage Supply20-240VFrequency (Hz)SOHzInsulation Thickness37	Number Of Shelf Positions	3
Number Of Baskets1Basket Size410x250x148Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR600aPlug TypeUKVoltage Supply20:240VFrequency (Hz)50HzInsulation Thickness37	Shelf Size	444 x 400
Basket Size410x250x148Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeUKVoltage Supply20-240VFrequency (Hz)50HzInsulation Thickness37	Shelf Material	PVC coated wire
Basket MaterialPVC coated wireInterior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeKeO0aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Number Of Baskets	1
Interior LightYesLight TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Basket Size	410x250x148
Light TypeLEDLight ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Basket Material	PVC coated wire
Light ActivationDoor Switch / ControllerFanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 · 32CRefrigerant TypeR600aPlug TypeUkVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Interior Light	Yes
FanYesSpark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 · 32CRefrigerant TypeR600aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Light Type	LED
Spark FreeNoDefrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 · 32CRefrigerant TypeR6O0aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Light Activation	Door Switch / Controller
Defrost SettingAutoController TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR6O0aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Fan	Yes
Controller TypeDigital / WirelessBattery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR6O0aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Spark Free	No
Battery Back UpYesController ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR600aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Defrost Setting	Auto
Controller ConnectivityWireless / SD DownloadNumber Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR600aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Controller Type	Digital / Wireless
Number Of Probes2Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR600aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Battery Back Up	Yes
Probe TypeAir / LoadAmbient Temperature Range10 - 32CRefrigerant TypeR600aPlug TypeUKVoltage Supply220-240VFrequency (Hz)50HzInsulation Thickness37	Controller Connectivity	Wireless / SD Download
Ambient Temperature Range 10 - 32C Refrigerant Type R600a Plug Type UK Voltage Supply 220-240V Frequency (Hz) 50Hz Insulation Thickness 37	Number Of Probes	2
Refrigerant Type R600a Plug Type UK Voltage Supply 220-240V Frequency (Hz) 50Hz Insulation Thickness 37	Probe Type	Air / Load
Plug Type UK Voltage Supply 220-240V Frequency (Hz) 50Hz Insulation Thickness 37	Ambient Temperature Range	10 - 32C
Voltage Supply 220-240V Frequency (Hz) 50Hz Insulation Thickness 37	Refrigerant Type	
Frequency (Hz) 50Hz Insulation Thickness 37	Plug Type	UK
Insulation Thickness 37		
	Frequency (Hz)	50Hz
Anti Microbial Handle Yes / BioCote	Insulation Thickness	37
	Anti Microbial Handle	Yes / BioCote







